

**PACKED WITH
SMARTNESS**

STAGE



25/30D/35DN-9V

500 mm load centre



ECONOMIC ENGINE
(-13% FUEL
CONSUMPTION)



**INTEGRATED
HYUNDAI
POWERTRAIN**



**ELECTRONIC
CONTROLLED
TRANSMISSION**



**FULL
CONTROL
CLUSTER**



**BEST
STANDARD
WARRANTY**

STAGE V AND BEYOND

Hyundai's new 9V Series is a smart generation of material handling diesel forklifts that comply with the European Stage V emission levels. But it goes much further than that!

In our mission, 'Moving you Further', Hyundai's engineers aimed for a **groundbreaking level of customer satisfaction** with **maximum performance** and **productivity**, higher **operator comfort**, better **safety** and **improved uptime management**.

Our new 9V forklifts feature a robust exterior design and are packed with performance-enhancing features that open up a world of new possibilities to tackle all the challenges you face in your logistics business.



PACKED WITH SMARTNESS

Productivity & Efficiency

POWERFUL AND FUEL-EFFICIENT TO REDUCE TCO (TOTAL COST OF OWNERSHIP)

The Hyundai engineers have left no stone unturned in their efforts to save you costs and improve your productivity. The Hyundai legacy of reliable technology continues with an optimised engine and powertrain, developed completely in-house in order to deliver unprecedented efficiency and boost your profits.


Unparalleled fuel efficiency NEW

V **STAGE** The 9V series is equipped with a powerful 2.2L HMC D4HB diesel engine that produces 47.7 KW while complying with European Stage V environmental regulations. It also achieves **impressive cost savings** by delivering excellent performance with low fuel consumption rates.



- Featuring the optimal displacement for a forklift, the HMC D4HB engine comprises a timing chain, an electronic EGR valve, a common rail, turbocharger with an excellent boosting effect and an exhaust gas after-treatment (DOC + DPF) device.
- A power mode selection switch is mounted on the dashboard. The operator can choose between lower power and lower fuel consumption or more power, depending on the application.
- The DPF regeneration works automatically.
- A parked regeneration can be activated manually at any time.
- The operator can use a switch to prevent the regeneration process (hot exhaust gases) for working in an area with a potential risk of fire.

Fuel efficiency
13%




New hydraulic system NEW


The new engine is combined with a new hydraulic pump and main control valve (MCV). The result is increased controllability, productivity and fuel efficiency.

Fuel consumption

Compared to our previous models -9 & -9E.



Based on VDI2198				
ENGINE	Manufacturer	MHC	KUBOTA	YANMAR
	Model	D4HB	V3307	4TNE92
	Emission Regulation	Stage 5	Stage 4	Stage 3
	Rated Power (ps/rpm)	65/2,300	67/2,200	45.5/2,450
	MAX Torque (kg-m/rpm)	24.1/1,500	23.1/1,500	14.4/1,600
	Displacement (cc)	2,199	3,331	2,659



Improved cooling system NEW


The new heavy-duty radiator with improved air-flow and increased volume **+13%** keeps the engine constantly within the optimal temperature range, even in harsh and tough applications.

Productivity & Efficiency

A LEGACY OF EXCELLENCE: HYUNDAI-DEVELOPED POWERTRAIN

The transmission and drive axle are developed entirely by Hyundai Core Motion for enhanced durability and practicality.

NEW The new electronically controlled transmission is fully adjustable in the cluster. This allows the set-up of the machine to any application.



The clutch pack boosts power transmission capability by 22% and increases T/M oil capacity for better efficiency in high-load working conditions.



FULL DIAGNOSTICS FOR SMOOTH OPERATIONS AND REDUCED COSTS

The 9V Series features an enhanced instrument cluster with an easy-to-use, full colour display enabling a full set-up, diagnostics and maintenance follow-up. More features like the DCSR system (prevents high-speed directional change) are available for activation. The DCSR system reduces tyre wear and protects the transmission in order to reduce operating and servicing costs.



NEW The drive axle is equipped with a planetary reducing gear offering resistance to torque changes. The sump capacity has been increased by 46% for better performance and durability of the wet disc brakes in environments requiring high brake usage. Thanks to its enhanced durability, the wet disc also reduces maintenance costs.



* Photo may include optional equipment.

Operator Comfort

OUTSTANDING ERGONOMICS FOR PRODUCTIVITY AND OPERATING PLEASURE

The cabin is designed to provide every operator with a comfortable working environment that boosts productivity and reduces fatigue, even in tough working conditions. The most important controls are positioned within easy reach and a range of options helps you to tailor the cabin to your needs.



* Photo may include optional equipment.

"I'm really impressed by how smooth and quiet it is. It's a completely different driving experience!"

Better visibility and cabin comfort

The mast, carriage, and head guard are designed to provide the operator with **maximum visibility** for improved efficiency and **peace of mind** while working.

A **premium quality Grammer** seat is installed as standard, ensuring a comfortable driving position all day, even in rough working conditions.

The **spacious full floating cabin** with air conditioning and/or heater is available as:

- Partial cabin
- 1-door or 2-door (split type) version

Several air-ducts, like the windshield defrosting air duct, are integrated in the headliner for perfect air-distribution inside the cabin for more comfort.



Cabin options **OPTION**



LED lights **OPTION**



The LED lights offer the optimal visibility under any conditions.

Rear grip **OPTION**

While driving backwards, the grip offers comfort to the operator. The integrated horn button increases safety.



Reduced steering wheel size **NEW**

The **steering wheel diameter** has been reduced by 70 mm to **minimise operator fatigue** and a Danfoss 4th generation Obitrol steering unit **reduces noise while improving rotation**.

Effect:

1. Reduced radius of rotation
2. Increased operator steering convenience



Operator Comfort

TECHNOLOGY AT YOUR FINGERTIPS FOR FULL CONTROL

The enhanced cluster makes it easier to manage and control all key functions. For best-in-class operating sensitivity, these stage V forklifts can be further equipped with fingertip control, allowing optimal usage and thus improving productivity.




Enhanced control cluster **NEW**

The enhanced instrument cluster makes it easier to manage the machine set-up, diagnostics and maintenance. All **settings can be entered directly into the cluster**, eliminating the need for an external computer.

- **Key monitoring functions:** OPSS, DPF replay, posture equipment maintenance, clock, service hour meter, fuel, temperature, driving direction and transmission level.
- **Configuration and diagnosis:** maximum driving speed, maintenance management, engine diagnosis, passcode setting.
- **Additional functions (option):** rear view camera, front & rear view cameras on separate monitor, load indicator, auto-tilting levelling.

The above functions are available in 13 languages via the cluster.



"The cabin is incredibly comfortable – everything is easy to reach, I have full control and I don't feel tired at all at the end of the day. The fingertip control is optional, but, honestly speaking, every customer should take it – so easy, precise and fully programmable."

Fine-tuned fingertip control for faster response **OPTION**



To ensure **top-class fingertip control**, Hyundai is partnered with **Buchholz**.

- The working speed of all functions is programmable in the cluster.
- The response time (within 0.1 s) and fine-tuning capability of fingertip control are improved, thanks to a high-end control system.
- The directional switch is integrated into the fingertip control for more comfort.

Better operating sensitivity



- The manual levers are in perfect reach for the driver, next to the operator's seat.
- The directional switch is integrated into the lift/lower lever for perfect ergonomics.
- The new Buchholz MCV offers a better controllability and a higher working speed which increases the productivity.

Safety

CREATING A SAFER WORKING ENVIRONMENT

Small details can make a huge difference when it comes to safety and security. By helping to ensure an accident-free workplace, the new 9V Series forklifts help you to achieve the peace of mind and productivity you need to safeguard your business.



Auto parking brake and hill start assist



The parking brake operates automatically when the power is disengaged in order to prevent accidents caused by human error. Hill Start Assist Control (HAC) prevents backsliding when restarting on a slope.

OPSS (Operator Presence Sensing System)



DRIVE LOCK LIFT LOCK TILT LOCK


The OPSS System restricts driving, lifting and tilting, and it kicks in automatically when the operator leaves the seat to prevent accidents. It operates in conjunction with the auto parking brake to contribute to a safer workplace.

Machine position warning



While driving the machine-control-unit (MCU) senses longitudinal and lateral movement and **alerts the driver if the preset stability values are exceeded.**

Seat belt interlock system OPTION



The seat belt interlock system protects operators from injury by **restricting equipment** operation if the seat belt warning has not been observed or if the operator unfastens the seat belt while driving.

Passcode-protected start-up

Operators can restrict machine operation by setting a passcode. This **prevents theft, break-ins or accidents** that could occur due to unauthorised access when the machine is not in use.

* Photo may include optional equipment.

Serviceability

BUILT FOR QUICK, EASY SERVICING

The peace of mind that comes with fast, low-effort servicing is also part of the Hyundai 9V Series philosophy. These forklifts are designed to make maintenance as convenient as possible. All components and materials have been optimised to ensure a long, trouble-free service life.



Easy maintenance

The wide opening angle of the engine hood in combination with tool-less removable panels **reduces equipment downtime** by providing easy access to parts requiring regular maintenance.



Easy inspection of the after-treatment device



For greater convenience, the counterweight opening has been made as large as possible. This **eliminates the need to remove the counterweight** for inspection or exchange of the after-treatment device.

Engine diagnostics and service scheduling

✕ Maintenance	
Engine Failure History	▶
Maintenance Management	▶
Signal Status	▶
User Password Change	▶

✕ Maintenance Management				
Item	Interval	Elapse	Count	Alarm
Axle Gear Oil	100	105	0	●
Transmissing Oil	100	105	0	●
Filter	100	105	0	●
Tank Air Breathe...	250	105	0	●
Engine Oil	500	105	0	●
Element	500	105	0	●

Engine and transmission failure codes can be checked in the cluster with **no need for a separate diagnostic tool**. Replacement timing for consumable parts is set in the cluster and informs the operator on the screen from 30h before scheduled maintenance service on the screen.

Convenient after-treatment device

The automatic DPF regeneration function is supported by a hydraulic device which maintain the exhaust gas temperature in order to secure the function of the DPF.

Water- and dustproof fuse and relay box



All fuses and relays are centralized in three boxes with **enhanced waterproof and dustproof protection IP65**. The boxes themselves are located behind the side cover panel for **quick access**.

Parts & Warranties

HYUNDAI GENUINE PARTS AND WARRANTIES: THE BEST WAY TO PROTECT YOUR INVESTMENT

Hyundai Genuine parts, accessories and warranty programmes are specially designed to keep your investment covered. They increase uptime and maintain the performance, comfort, and convenience that are built into your equipment.



Leader in standard warranties for Stage V forklifts!

Hyundai warranties are designed to give you the cover you need to build your business with confidence and peace of mind.

Best standard warranties in the industry

For extra reassurance, and to ensure maximum customer confidence, we are supplying all new stage V models with best industry standard warranties.

The **powertrain standard warranty** has been extended by **33%**, from **3,000 to 4,000 hours**.*

The forklift **standard warranty** covers you for **two years or 3,000 hours, whichever comes first**.

Powertrain standard warranty
33% ↑



Forklift standard warranty*
2 years

*or 3,000 hours, whichever comes first.

Optional and extended warranty periods

In addition to this standard coverage, optional and extended warranty periods are available, allowing you to benefit from full warranty coverage for longer, and even over the full service life of your forklift.*

Hyundai Genuine parts

Hyundai Genuine parts have the same design as those installed when your machine left the factory. They are subjected to rigorous quality inspections and tests to make sure they meet Hyundai's

strict requirements for quality and durability. As well as minimising downtime, this helps to ensure peak performance in every task. In the 13,000 m² warehouse, **Hyundai covers over 96% of all Genuine Parts**. With one of Europe's most advanced automated warehousing systems, we are able to maintain availability and efficient delivery of all our Genuine Parts.

A network you can rely on

HCEE prioritises quick, reliable intervention to keep your equipment running reliably. Thanks to the **extended dealer network across Europe, we will always be close by to ensure a timely and efficient solution**. Moreover, we guarantee a 24-hour delivery service across our European dealer network.

*Conditions apply. Please discuss the optimal solution for your needs with your dealer.

Specifications

25/30D - 35DN-9V

Distinguishing marks				Hyundai	Hyundai	Hyundai
1.1	Manufacturer			Hyundai	Hyundai	Hyundai
1.2	Manufacturer's Model Designation			25D-9V	30D-9V	35DN-9V
1.3	Drive			Diesel	Diesel	Diesel
1.4	Type Of Operation			Seated	Seated	Seated
1.5	Load Capacity	C	kg	2,500	3,000	3,500
1.6	Load Centre Distance	x	mm	500	500	500
1.8	Load Distance (Centre of Drive Axle to Fork)	y	mm	468	468	468
1.9	Wheelbase		mm	1,650	1,700	1,700
2.1	Service Weight		kg	3,871	4,300	4,616
2.2	Axle Loading, Loaded	Front / Rear	kg	5,548 / 823	6,349 / 951	7,080 / 1,035
2.3	Axle Loading, Unloaded	Front / Rear	kg	1,581 / 2,290	1,641 / 2,659	1,588 / 3,028
3.1	Tyres			Pneumatic	Pneumatic	Pneumatic
3.2	Tyre Size	Front		7.00-12-12PR	8.15-15-14PR	8.15-15-14PR
3.3	Tyre Size	Rear		6.50-10-12PR	6.50-10-12PR	6.50-10-12PR
3.5	Number of Wheels (x = Driven Wheels)	Front / Rear		2 x 2	2 x 2	2 x 2
3.6	Tread	Front	mm	999	1,005	1,005
3.7	Tread	Rear	mm	980	980	980
4.1	Tilt of Mast / Fork Carriage Forward / Backward	α / β	degree	6 / 10	6 / 10	6 / 10
4.2	Height, Mast Lowered	h1	mm	2,175	2,190	2,260
4.3	Free Lift	h2	mm	155	155	155
4.4	Lift Height	h3	mm	3,305	3,305	3,305
4.5	Height, Mast Extended	h4	mm	4,485	4,485	4,485
4.7	Height of	Overhead Guard	h5	2,160	2,180	2,180
		Cabin		2,170	2,190	2,190
4.8	Seat Height / Stand Height Rel. to SIP	h7	mm	1,187	1,207	1,208
4.12	Coupling Height	h10	mm	310	300	295
4.19	Overall Length	l1	mm	3,672	3,751	3,816
4.20	Length to Face of Forks	l2	mm	2,622	2,701	2,756
4.21	Overall Width	b1	mm	1,200	1,230	1,230
4.22	Fork Dimensions	l x e x s	mm	45 x 100 x 1050	45 x 122 x 1050	45 x 122 x 1050
4.23	Fork Carriage ISO 2328, Class / Type A, B			2A	3A	3A
4.24	Fork-Carriage Width	b3	mm	1102	1102	1102
4.31	Ground Clearance, Below Mast, Loaded	m1	mm	130	145	145
4.32	Ground Clearance, Centre of Wheelbase	m2	mm	172	171	171
4.34.1	Aisle Width For Pallets 1000 X 1200 Crossways	Ast	mm	4,020	4,095	4,148
4.34.2	Aisle Width For Pallets 800 X 1200 Lengthways	Ast	mm	4,220	4,295	4,348
4.35	Turning Radius	Wa	mm	2,352	2,427	2,480
4.36	Smallest Pivot Point Distance		mm	714	731	731
5.1	Travel Speed	Loaded / Unloaded	km/h	16.4 / 17.7	17.2 / 18.8	16.9 / 18.8
5.2	Lift Speed	Loaded / Unloaded	mm/s	580 / 610	580 / 610	480 / 500
5.3	Lowering Speed	Loaded / Unloaded	mm/s	510 / 500	550 / 500	510 / 480
5.6	Max. Drawbar Pull	Loaded / Unloaded	N	27,399 / 25,957	25,777 / 24,257	26,016 / 24,162
5.8	Max. Gradeability	Loaded / Unloaded	%	42.7 / 21.5	34.1 / 20.1	30.6 / 17.7
5.10	Service Brake			Hydraulic	Hydraulic	Hydraulic
7.1	Engine Manufacturer / Type			HMC D4HB	HMC D4HB	HMC D4HB
7.2	Engine Power Acc. to ISO 1585		kW / rpm (hp / rpm)	47.8 / 2,300 (64.1 / 2,300)	47.8 / 2,300 (64.1 / 2,300)	47.8 / 2,300 (64.1 / 2,300)
7.3	Maximum Torque		kgf.m / rpm	24.1 / 1,600	24.1 / 1,600	24.1 / 1,600
7.4	No. of Cylinders / Displacement		EA / cc	4 / 2199	4 / 2199	4 / 2199
7.5	Fuel Consumption Acc. to Vdi Cycle		l/h	2.7	3	3.2
8.1	Type of Drive Control		AC	Power Shift	Power Shift	Power Shift
8.2	Operating Pressure, System / Attachments		bar	200 / 140	200 / 140	200 / 140
8.3	Oil Volume For Attachments		LPM	55	55	55
8.5	Trailer Coupling, Type Din			PIN	PIN	PIN

* The above specifications are based on V300 mast.

* In accordance with guideline 2198, this specification sheet provides details of the standard truck only. Non-standard tyres, different masts, optional equipment, etc., may result in different values.

STANDARD AND OPTIONS

	Part	Description	25D-9V	30D-9V	35DN-9V	
Operation room	OHG	Overhead Guard *25D-9V : 2,160mm, 30D-9V & 35DN-9V : 2,180mm	●	●	●	
		Overhead guard with Rain Cover *25D-9V : 2,170mm, 30D-9V & 35DN-9V : 2,190mm	○	○	○	
	Cabin	Cabin Options - One door, Two door	○	○	○	
		Partial Cabin - Front glass with Wiper, Rear glass & Top Rain Cover	○	○	○	
	A/C	Air Conditioner and / or Heater	○	○	○	
		The air conditioning system contains fluorinated greenhouse gas refrigerant R134a. (Global Warming Potential: 1,430) The system contains 0.55 kg refrigerant representing a CO ₂ equivalent of 0.787 metric tonnes.	○	○	○	
	Seat	Full Suspension Synthetic leather Seat + Orange Belt, Arm Rest, Seat Switch	●	●	●	
		Seat Accessories - Long Backrest, Belt Switch, Heated Seat	○	○	○	
	Lever	Lever - General	●	●	●	
		Lever - Fingertip control	○	○	○	
Ect.	Radio & USB	○	○	○		
	Rear Horn Grip	●	●	●		
Mast & attachment	Mast	2 Stage mast - Standard (V)	●	●	●	
		2 Stage mast - Single full free (VF)	○	○	○	
		3 Stage mast - Single full free (TF), Dual full free (TS)	○	○	○	
	Fork	1,200mm Fork	●	●	●	
		Fork Options - 900mm-2,300mm	○	○	○	
	Carriage	Carriage - Narrow (1,102mm / Hook)	●	●	●	
Carriage Options Wide (1,442mm / Hook)		○	○	○		
Attachment	Hook-on Side Shift	○	○	○		
	Integrated Side-Shift	○	○	○		
	Side-Shift & Fork Positioner	○	○	○		
Hydraulics	MCV & Hoses	3 Spool MCV + attached piping for V330 mast	●	●	●	
		MCV Options - 4 Spool	○	○	○	
		Attached Piping for All MCVs & Masts	○	○	○	
		Brake - General type	●	●	●	
Tyres	Tyres	Tyre - Pneumatic (Single)	●	●	●	
		Tyre Options	Solid	○	○	○
			Non Marking	○	○	○
			Pneumatic Double or Solid Double tyre (15" wheel rim)	○	○	○
Visibility	Lamp	Working Lamp - Front Bulb	●	●	●	
		Working Lamp Options - Front LED, Rear LED	○	○	○	
		Rear Blue Spot	○	○	○	
		LED Beacon Lamp	○	○	○	
	Mirror	Mirror - Panorama	●	●	●	
Mirror Options - L/H & R/H Back Mirror, Outside Mirror		○	○	○		
Camera	Rear View Camera only	○	○	○		
	Front & Rear View Camera	○	○	○		
Convenience	-	Knob-Switch with Direction & Horn	●	●	●	
		Auto Tilt Levelling	○	○	○	
		Load Indicator	○	○	○	
Safety	-	Hydraulic Pressure Indication On Display	●	●	●	
		OPSS - Travel & Mast	●	●	●	
		Master Switch to cut-off electricity from battery	●	●	●	
Others	-	Hazard Switch	○	○	○	
		Steel Side Cover	○	○	○	
		Plastic Side Cover	●	●	●	
		Recycling Option (Rear Tyre Cover + Under Cover)	○	○	○	
		Fuel Cap with Key	○	○	○	
		Pre-cleaner	○	○	○	
		Hyd. Oil-VG46	●	●	●	
		Hyd. Oil Options - VG68 for Tropical, VG15 & VG32 for Cold Area	○	○	○	
Accumulator - Mast damping	○	○	○			

● : STD / ○ : OPT



*Standard and optional equipment may vary by country. Contact your Hyundai dealer for more information. *The machine may vary according to International standards. European specifications may differ from Korean specifications mentioned in the brochures. *The photos may include attachments and optional equipment that are not available in your area. * Materials and specifications are subject to change without advance notice. *All imperial measurements rounded off to the nearest pound or inch.

Hyundai Construction Equipment Europe NV
Hyundailaan 4, 3980 Tessenderlo, Belgium
Tel: (+32) 14-56-2200 Fax: (+32) 14-59-3405

Contact your Hyundai dealer.
hyundai-mh.eu

Address